

CARACTERÍSTICAS TÉCNICAS LINEA LABORATORIO/LABORATORY LINE "GAMA TOP" SERIE G

GAMA	TOP	TOP	TOP	TOP	TOP
MODELO	LTR17G	LTR25G	LTR40G	LTR70G	LTR140G
Capacidad Nominal (litros)/Nominal Capacity (liters)	170	250	400	610	1340
Rango T ³	+2 // +8	+2 // +8	+2 // +8	+2 // +8	+2 // +8
Largo Exterior (mm)/Exterior Length	670	670	670	687	1385
Profundidad Exterior (mm)/Exterior Deep	655	655	655	795	795
Altura Exterior (mm)/Exterior Heigh	1285	1530	1955	2130	2130
Largo Interior (mm)/Interior Length	570	570	570	577	1275
Profundidad Interior (mm)/Interior Deep	480	480	480	690	690
Altura Interior (mm)/Interior Heigh	800	1045	1470	1529	1529
Espesor Aislamiento (mm)/Insulation thickness	50	50	50	55	55
Acabado Exterior/Exterior finishing	Acero plastificado Plasticized steel	Acero plastificado Plasticized steel	Acero plastificado Plasticized steel	Acero plastificado Plasticized steel	Acero plastificado Plasticized steel
Acabado Interior/Interior finishing	Acero plastificado Plasticized steel	Acero plastificado Plasticized steel	Acero plastificado Plasticized steel	Inox Inox	Inox Inox
Nº Estantes / Cajones/Shelves / Drawers number	3	4	8	8	16
Dimensiones Estante/Cajon (LxP)/Shelf / Drawer size	495 x 448	495 x 448	495 x 448	505 x 518	505 x 518
Material Estantes/Cajones/Shelves / Drawers material	Acero pintado epoxi Epoxi coated steel	Acero pintado epoxi Epoxi coated steel	Acero pintado epoxi Epoxi coated steel	Inox Inox	Inox Inox
Intercambiabilidad de estantes/cajones/Interchangeable Shelves / Drawers	●	●	●	●	●
Tipo de Puerta/Door type	Cristal/Glass	Cristal/Glass	Cristal/Glass	Cristal/Glass	Cristal/Glass
Estilo de Puerta/Door style	Abatible, reversible Swing, reversible	Abatible, reversible Swing, reversible	Abatible, reversible Swing, reversible	Abatible, reversible Swing, reversible	Abatible, reversible Swing, reversible
Sensor de Puerta/Door sensor	●	●	●	●	●
Cerradura/Lock	●	●	●	●	●
Tipo de Controlador/Controller type	Digital pantalla grafica Digital graphic display	Digital pantalla grafica Digital graphic display	Digital pantalla grafica Digital graphic display	Digital pantalla grafica Digital graphic display	Digital pantalla grafica Digital graphic display
Salida USB/USB port	●	●	●	●	●
Datalogger/Datalogger	●	●	●	●	●
Bateria/Battery	■	▲	■	■	■
Sonda simulación producto/Product temperature simulation probe	▲	▲	▲	▲	▲
Termostato anticongelación/Freezing protection controller	▲	▲	▲	▲	▲
Patas ajustable en altura/Height adjustable legs	●	●	●	●	●
Opción Ruedas/Optional caster	●	●	●	●	●
Luz/Light	●	●	●	●	●
Ventilador evaporador/Evaporator fan	●	●	●	●	●
Tipo de Condensación/Condensation type	Ventilada/Ventilated	Ventilada/Ventilated	Ventilada/Ventilated	Ventilada/Ventilated	Ventilada/Ventilated
Tipo de desescarche/Defrost type	Automático/Automatic	Automático/Automatic	Automático/Automatic	Automático/Automatic	Automático/Automatic
Evaporación automatica agua desescarche/Automatic defrost water evaporation	●	●	●	●	●
Clase Climatica/Climatic class	N+32	N+32	N+32	N+32	N+32
Refrigerante/Refrigerant	R134a	R134a	R134a	R134a	R134a
Disponibilidad de otros tipo de clavija/ Other specific plugs (optional)	●	●	●	●	●
Tension/Fases/Frecuencia/Voltage/Phases/Frecuency	230/50	230/50	230/50	230/50	230/50
Potencia Electrica (W)/Electric power	278	315	305	520	520

● SI/YES ● SI/YES

■ NO

▲ Opcional/Optional